


**Test Report Number:** ETRB40717  
**Reference Standard:** CFR Title 47, FCC Part 15, Class A  
ICES-003, Issue 5, August 2012  
**Date of Test:** 28 July 2014  
**Date of Report:** 30 July 2014  
**Product Name:** STX250-1  
**Model Number:** STX250-1  
**Serial Number:** 443VX  
**Manufacturer:** Tensitron  
**Representative:** Chris Crosby  
**Report Type:** Radiated and Conducted Emissions  
**Test Result:** Compliant  
**Approved By:** 

**FCC**

DN: US5316  
TSRN: 735190  
FRN: 0015264914

**BSMI**

SL2-IN-E-1134R

**VCCI**

Member #: 2649  
Registration #: A-0170  
R-3273 C-3642  
T-1756 G-233

**MSIP**

US0168

**MIC**

US0168

EMC Integrity, Inc. is an electromagnetic interference and compatibility test lab that is accredited by NVLAP (Lab Code 200737). EMCI's certificate and scope of accreditation are contained in the "Laboratory Accreditations" appendix of this report.

EMC Integrity, Inc. is a Nemko partner lab (ELA-215), and the Nemko certificate and scope of accreditation are contained in the "Laboratory Accreditations" appendix of this report.

The results contained within this report relate only to the product tested. In the event of a discrepancy between EMCI's master report and the report delivered to the client, the EMCI report shall take precedence.

This report shall not be reproduced, except in full, without written approval from EMC Integrity, Inc.

This report must not be used by the client to claim product certification, approval, or endorsement by EMC Integrity, NEMKO, NVLAP, NIST, or any agency of the federal government.

**Prepared for:**

Tensitron  
733 South Bowen Street  
Longmont, Colorado 80501  
Phone: (303) 415-1112  
Fax: (720) 306-4445

**Customer Representative:**

Chris Crosby  
President

**Tested at:**

EMC Integrity, Inc.  
1736 Vista View Drive  
Longmont, Colorado 80504

**Tested by:**

Kevin Johnson  
Test Engineer

**Report Prepared by:**

Mary Burback  
Office Manager

**Report Approved by:**

Vincent Greb  
Laboratory Manager

Revision	Description of Revision	Date:
Rev. -	Initial Release	30 July 2014

## **TABLE OF CONTENTS**

	<b>Section #</b>
<b>Test Summary .....</b>	<b>1.0</b>
<b>Test Environment.....</b>	<b>2.0</b>
<b>Radiated Emissions .....</b>	<b>3.0</b>
<b>Conducted Emissions.....</b>	<b>4.0</b>

## **LIST OF APPENDICES**

<b>Radiated Emissions Test Data .....</b>	<b>APPENDIX A</b>
<b>Conducted Emissions Test Data .....</b>	<b>APPENDIX B</b>
<b>Product Data Sheet .....</b>	<b>APPENDIX C</b>
<b>EMI Test Log.....</b>	<b>APPENDIX D</b>
<b>Laboratory Accreditations.....</b>	<b>APPENDIX E</b>

## 1.0 TEST SUMMARY

### 1.1 Product Description

The unit under test (UUT) was the STX250-1. The model number tested was STX250-1 and the serial number tested was 443VX. It is manufactured by Tensitron located in Longmont, Colorado. This product is an electronic tension gauge designed for use in industrial locations. The product was continually exercised during testing, as documented in the “configuration” field of the test data sheet.

Additional information regarding this product may be found in the Product Data Sheet, located in Appendix C of this report.

### 1.2 Purpose

This report documents the test efforts performed on the STX250-1 to verify compliance to the Class A limits of FCC Part 15 and ICES-003. This was a formal qualification test and was conducted on 28 July 2014.

### 1.3 Test Standards Used

The emission limits applied to the product tested are defined in CFR Title 47, FCC Parts 15.107 and 15.109. This is the U.S. document which governs electromagnetic emissions from computing devices for conducted and radiated emissions, respectively. The UUT was set up as specified in ANSI C63.4: 2009.

The normative references of this standard define the test methods used for the emissions testing. These standards are contained in Table 1-1.

**Table 1-1**

CFR Title 47 FCC Part 15	ICES-003, Issue 5, August 2012
ANSI C63.4: 2009	

### 1.4 Test Results

The UUT **complied** with the Class A emission requirements defined in Table 1-1. Test data is contained in the appropriate appendices of this report.

### 1.5 Modifications Required for Compliance

None.

## 2.0 TEST ENVIRONMENT

### 2.1 Radiated Emissions Test Site

Radiated emissions testing was performed at a distance of 10-meters in a semi-anechoic 10-meter chamber. This chamber is calibrated annually and meets the volumetric site attenuation requirements of ANSI C63.4. For measurements from 30 MHz to 1 GHz, a biconilog antenna is used in conjunction with a high-gain, low-noise preamplifier. This is connected to an HP 8566B spectrum analyzer with an HP 85650A Quasi-Peak (QP) Adapter, via an HP 85685 RF Preselector.

Radiated emissions testing is broken into two parts: pre-scan and QP/maximization. Pre-scanning a product from 30 MHz to 1 GHz consists of measuring peak emissions from eight radials (every 45 degrees), at four antenna heights (1 m, 2 m, 3 m and 4 m) for both antenna polarities. Data is recorded in a graph showing amplitude vs. frequency of the emissions, and frequencies for QP/maximization are chosen based on this graph. The procedure for maximizing emissions is as follows:

1. The analyzer is tuned to the frequency associated with the emissions having the least margin.
2. The turntable and antenna mast are moved to the location where the maximum emission was measured during the pre-scan.
3. Both are then oriented such that the maximum emission is obtained.
4. Cables on the UUT are manually manipulated to achieve the maximum emission.
5. The turntable and antenna mast are then re-adjusted to ensure a maximum reading.
6. If the signal in question is less than 1 GHz, quasi-peak detection is performed on the signal for a minimum of 10 seconds. For signals greater than 1 GHz, video averaging is performed.
7. Turntable/antenna mast maximization and QP detection are performed on all other signals within 6 dB of the limit. In the event that there are not six signals within 6 dB of the limit, the highest six signals are maximized. This ensures that a minimum of six signals are maximized and appear in the final data table.

For emission measurements above 1 GHz, the antenna is changed to a double-ridged horn equipped with a preamplifier and run directly into the spectrum analyzer. The antenna spacing is reduced from 10 meters to 3 meters and RF absorber is placed on the floor between the antenna and the UUT such that the site VSWR requirements of CISPR 16 are achieved. The QP adapter and RF preselector are not used above 1 GHz.

Pre-scanning a product from 1-18 GHz is performed similarly, except that 16 radials (every 22.5 degrees) and three antenna heights (1 m, 1.5 m and 2 m) are used. A similar maximization process is used as for the lower frequency range, except that average measurements are performed, rather than QP measurements.

## 2.2 Conducted Emissions Test Site

Conducted emissions testing was performed on a 10' by 10' ground plane, which is bonded to the wall of the 10-meter chamber, using its wall as the vertical coupling plane. Line impedance stabilization networks (LISNs) was inserted in series with both the UUT and the support equipment. The LISNs used were standard 50  $\Omega$ /50 uH LISNs which complied with the requirements of ANSI C63.4. These LISNs are calibrated annually for both complex impedance and insertion loss. Measurement equipment used was an HP 8566B spectrum analyzer with an HP 85650A QP adapter. In addition, a transient limiter and a high-pass filter are used to protect the front-end of the receiver from transients and low-frequency noise, respectively.

## 2.3 Measurement Uncertainty

The measurement uncertainty for EMC Integrity's emissions test facility complies with the requirements defined in CISPR 16. The complete calculations of EMC Integrity's measurement uncertainty is contained in an EMCI memo, which is available upon request. However, a summary of EMCI's measurement uncertainty is given in Table 2-1.

**Table 2-1**

<b>Test</b>	<b>Requirement</b>	<b>Actual</b>
Conducted Emissions	3.60 dB	3.04 dB
Radiated Emissions – Horizontal Polarity	5.20 dB	4.67 dB
Radiated Emissions – Vertical Polarity	5.20 dB	5.01 dB

### **3.0 Radiated Emissions**

#### **3.1 Summary of Test Results**

Radiated electric field emissions were measured on the UUT over the frequency range from 30 MHz to 30 GHz. The UUT was powered from 120 Vac/60 Hz, configured in its normal operating mode, and exercised continually during testing. Cables were oriented such that the maximum emission was achieved and quasi-peak detection was performed all signals (minimum of six) used in the final data table. Average detection was performed for all signals that were maximized above 1 GHz.

Test result:       Compliant  
Margin:            15.45 dB @ 12709.982 MHz

#### **3.2 Test Setup**

The UUT was set up in accordance with ANSI C63.4 and tested to the Class A limits specified for unintentional transmitters in FCC 15.109.

#### **3.3 Special Configurations**

Not applicable.

#### **3.4 Deviations from Test Procedures**

Not applicable.

#### **3.5 Test Data**

See APPENDIX A for all test data sheets, test setup pictures and test equipment used.

## **4.0 Conducted Emissions**

### **4.1 Summary of Test Results**

Conducted emissions were measured on the AC power input of the UUT over the frequency range from 150 kHz to 30 MHz. With the UUT configured in its normal operating mode, testing was performed with UUT powered from 120 Vac/60 Hz. The input power to both the UUT and the support equipment was run through standard 50  $\Omega$ /50  $\mu$ H line impedance stabilization networks (LISNs) which complied with the requirements of ANSI C63.4. Emissions were compared to both quasi-peak (QP) and average limits, with QP detection and averaging performed on the six highest signals.

Test result:      Compliant  
Margin:            23.69 dB @ 0.151 MHz

### **4.2 Test Setup**

The UUT was set up in accordance with ANSI C63.4 and tested to the Class A limits specified for unintentional transmitters in FCC 15.107.

### **4.3 Special Configurations**

Not applicable.

### **4.4 Deviations from Test Procedures**

Not applicable.

### **4.5 Test Data**

See APPENDIX B for all test data sheets, test setup pictures and test equipment used.



## **APPENDIX A**

### **Radiated Emissions Test Data**



## Radiated Emissions, FCC Part 15

Manufacturer:	Tensitron	Project Number:	B40717
Customer Representative:	Chris Crosby	Test Area:	10m1
Model:	STX250-1	S/N:	443VX
Standard Referenced:	FCC Part 15	Date:	July 28, 2014
Temperature:	23°C	Humidity:	67%
Input Voltage:	120Vac/60Hz	Pressure:	845mb
Configuration of Unit:	Pre-set load reading		
Test Engineer:	Kevin Johnson		

B40717-11-RE.doc

FR0100

Type	Frequency (MHz)	Level (dBuV)	Transducer (dB/m)	Gain / Loss (dB)	Final (dBuV/m)	Azm(deg)/Pol/Hgt(m)	Margin: FCC Class A QP (dB)	Margin: FCC Class A AV (dB)
QP	31.052	25.0	20.3	-28.1	17.2	8/V-Pole/2.28	21.89	-
QP	72.347	32.0	8.4	-27.6	12.8	235/V-Pole/1.54	26.31	-
QP	91.372	37.9	8.2	-27.6	18.5	103/V-Pole/4.00	24.96	-
QP	158.712	28.6	12.1	-27.3	13.4	18/V-Pole/2.39	30.06	-
QP	191.419	27.9	11.4	-27.2	12.1	199/H-Pole/3.71	31.39	-
QP	198.628	34.2	12.3	-27.2	19.3	264/V-Pole/1.00	24.16	-
QP	903.994	24.3	22.4	-24.5	22.3	219/H-Pole/1.00	24.12	-
QP	988.478	24.1	22.9	-24.2	22.8	236/H-Pole/3.29	26.71	-
Type	Frequency (MHz)	Level (dBuV)	Transducer (dB/m)	Gain / Loss (dB)	Final (dBuV/m)	Azm(deg)/Pol/Hgt(m)	Margin: EN55022+FCC 3m Class A 1-40GHz PK (dB)	Margin: EN55022+FCC 3m Class A 1-40GHz AV (dB)
AV	6445.444	54.9	34.7	-53.6	36.0	284/V-Pole/1.00	-	24.50
PK	6445.444	67.5	34.7	-53.6	48.6	284/V-Pole/1.00	31.85	
AV	9357.563	55.6	38.5	-57.4	36.7	183/V-Pole/1.00	-	23.79
PK	9357.563	68.1	38.5	-57.4	49.2	183/V-Pole/1.00	31.29	
AV	12709.982	55.8	39.5	-50.2	45.0	176/V-Pole/1.00	-	15.45
PK	12709.982	68.9	39.5	-50.2	58.2	176/V-Pole/1.00	22.30	
AV	13210.941	55.1	40.1	-53.1	42.1	62/H-Pole/1.00	-	18.39
PK	13210.941	68.1	40.1	-53.1	55.1	62/H-Pole/1.00	25.39	
AV	13704.429	53.4	40.8	-51.9	42.2	107/V-Pole/1.13	-	18.22
PK	13704.429	66.1	40.8	-51.9	55.0	107/V-Pole/1.13	25.47	
AV	14326.248	51.6	41.9	-51.8	41.7	173/V-Pole/1.54	-	18.72
PK	14326.248	64.6	41.9	-51.8	54.7	173/V-Pole/1.54	25.72	

The highest emission measured was at **12709.982 MHz**, which was **15.45 dB** below the limit.

<p>➤ “Type” refers to the type of measurement performed. The type of measurement made is based on the requirements of the particular standard:</p> <ul style="list-style-type: none"> <li>PK = Peak Measurement: RBW is 120kHz, VBW is 3 MHz</li> <li>QP = Quasi-Peak Measurement: RBW is 120kHz, VBW is 3 MHz, and QP Detection is ENABLED</li> <li>AV = Video Average Measurement: RBW is 1 MHz, VBW is 10 Hz</li> </ul> <p>➤ The “Final” emissions level is attained by taking the “Level” and adding the “Transducer” factor and the “Gain/Loss” factor. Final measurements are made with the Azimuth, Polarity, Height, and EUT Cables positioned for maximum radiation. If applicable, cables positions are noted in the test log. (Sample Calculation: 49.6 dBuV + 11.4 dB/m – 28.8 dB = 32.2 dBuV/m. <b>Important Note:</b> This is a sample calculation only for the purpose of demonstration, and does not reflect data in this report.)</p> <p>➤ The “Azm/Pol/Hgt” indicates the turn-table <i>azimuth</i>, the antenna <i>polarity</i>, and the antenna <i>height</i> where the</p>
---

EMC INTEGRITY, INC.  
Test Report # ETRB40717

maximum emissions level was measured.

- The “Margin” is with reference to the emissions limit. A positive number indicates that the emission measurement is below the limit. A negative number indicates that the emission measurement exceeds the limit.
- The PRESCAN is a peak measurement and is performed with the RBW set to 120 kHz, VBW set to 3 MHz (30 MHz to 1 GHz), and the RBW set to 1 MHz, VBW set to 100 kHz ( $> 1$  GHz)



## Radiated Emissions, FCC Part 15

Manufacturer: Tensitron  
Customer Representative: Chris Crosby  
Model: STX250-1  
Standard Referenced: FCC Part 15

Project Number: B40717  
Test Area: 10m1  
S/N: 443VX  
Date: July 28, 2014

B40717-11-RE.doc

FR0100




Figure A1: Radiated Emissions Prescan, 30MHz to 1000MHz, Peak Measurements at 10m Distance



## Radiated Emissions, FCC Part 15

Manufacturer: Tensitron  
Customer Representative: Chris Crosby  
Model: STX250-1  
Standard Referenced: FCC Part 15

Project Number: B40717  
Test Area: 10m1  
S/N: 443VX  
Date: July 28, 2014

B40717-11-RE.doc

FR0100




Figure A2: Radiated Emissions Prescan, 1GHz to 18GHz, Peak Measurements at 3m Distance



## Radiated Emissions, FCC Part 15

Manufacturer: Tensitron  
Customer Representative: Chris Crosby  
Model: STX250-1  
Standard Referenced: FCC Part 15

Project Number: B40717  
Test Area: 10m1  
S/N: 443VX  
Date: July 28, 2014

B40717-11-RE.doc

FR0100




Figure A3: Radiated Emissions Prescan, 18Hz to 30GHz, Peak Measurements at 1m Distance

## Radiated Emissions, FCC Part 15

Manufacturer: Tensitron  
Customer Representative: Chris Crosby  
Model: STX250-1  
Standard Referenced: FCC Part 15

Project Number: B40717  
Test Area: 10m1  
S/N: 443VX  
Date: July 28, 2014

B40717-11-RE.doc

FR0100



Figure A4: Radiated Emissions Test Setup - Front

## Radiated Emissions, FCC Part 15

Manufacturer: Tensitron  
Customer Representative: Chris Crosby  
Model: STX250-1  
Standard Referenced: FCC Part 15

Project Number: B40717  
Test Area: 10m1  
S/N: 443VX  
Date: July 28, 2014

B40717-11-RE.doc

FR0100



Figure A5: Radiated Emissions Test Setup - Right



## Radiated Emissions, FCC Part 15

Manufacturer: Tensitron  
Customer Representative: Chris Crosby  
Model: STX250-1  
Standard Referenced: FCC Part 15

Project Number: B40717  
Test Area: 10m1  
S/N: 443VX  
Date: July 28, 2014

B40717-11-RE.doc

FR0100




Figure A6: Radiated Emissions Test Setup - Back

## Radiated Emissions, FCC Part 15

Manufacturer:	Tensitron	Project Number:	B40717
Customer Representative:	Chris Crosby	Test Area:	10m1
Model:	STX250-1	S/N:	443VX
Standard Referenced:	FCC Part 15	Date:	July 28, 2014

B40717-11-RE.doc FR0100



Figure A7: Radiated Emissions Test Setup – Left

## Radiated Emissions, FCC Part 15

Manufacturer:	Tensitron
Customer Representative:	Chris Crosby
Model:	STX250-1
Standard Referenced:	FCC Part 15

B40717-11-RE.doc

Project Number:	B40717
Test Area:	10m1
S/N:	443VX
Date:	July 28, 2014

FR0100




Figure A8: Radiated Emissions Test Setup – 3m



## Radiated Emissions, FCC Part 15

Manufacturer:	Tensitron	Project Number:	B40717
Customer Representative:	Chris Crosby	Test Area:	10m1
Model:	STX250-1	S/N:	443VX
Standard Referenced:	FCC Part 15	Date:	July 28, 2014

B40717-11-RE.doc

FR0100

## Test Equipment List

ID Number	Manufacturer	Model #	Serial #	Description	Cal Date	Cal Due
1030	EMCO	3115	9906-5816	Double-ridged Horn (1 - 18 GHz)	04/28/2014	04/28/2015
1197	EMCO	3116	00040962	DRG Horn 18-40 GHz	11/12/2013	11/12/2014
1219	Mini-Circuits	ZKL-2	062905	Preamp, 10 - 2000 MHz, 30 dB	01/22/2014	01/22/2015
1223	Hewlett Packard	85650A	3303A01859	Quasi-Peak Adaptor	03/13/2014	03/13/2015
1231	Sunol Sciences	JB1	A071605-1	Bilog Antenna, 30 MHz to 2.0 GHz	11/27/2013	11/27/2014
1233	Sunol Sciences	SC104V	110305-1	Positioning Controller	NA	NA
1234	CIR Enterprises	10m Chamber	001	10m Chamber with 2.5m turntable	11/17/2013	11/17/2014
1238	Sunol Sciences	TWR95-4	110305-3	Antenna Mast	NA	NA
1239	Sunol Sciences	FM2522VS	110305-2	Turn Table, 2.5m Diameter	07/29/2013	07/29/2014
1253	Narda West	1840N506	010-100	18 to 40 GHz Preamplifier, 40dB Gain Nominal	02/17/2014	02/17/2015
1266	California Instruments	MX15-1	57961	AC Power Source, 0 - 300 VAC / 16 - 819 Hz / 15kVA	NA	NA
1276	Narda	DBL-0218N308	037-038	1GHz to 18GHz Preamplifier, 60dB gain nominal	05/09/2014	05/09/2015
1335	Hewlett Packard	85662A	2542A10937	Spectrum Analyzer Display	03/13/2014	03/13/2015
1336	Hewlett Packard	8566B	2532A02062	Spectrum Analyzer RF Section	03/13/2014	03/13/2015

## **APPENDIX B**

### **Conducted Emissions Test Data**



## Conducted Emissions, FCC Part 15

Manufacturer:	Tensitron	Project Number:	B40717
Customer Representative:	Chris Crosby	Test Area:	10m1
Model:	STX250-1	S/N:	443VX
Standard Referenced:	FCC Part 15	Date:	July 28, 2014
Temperature:	24°C	Humidity:	67%
Input Voltage:	120Vac/60Hz	Pressure:	845mb
Configuration of Unit:	Pre-set load reading		
Test Engineer:	Kevin Johnson		

B40717-11-CE.doc

FR0100

Type	Frequency (MHz)	Level (dBuV)	Transducer (dB)	Gain / Loss (dB)	Final (dBuV)	Test Point	Margin: FCC Class A AV (dB)	Margin: FCC Class A QP (dB)
AV	0.151	27.6	-1.3	16.0	42.3	Line 1	23.69	-
QP	0.151	31.6	-1.3	16.0	46.3	Line 1	-	32.73
AV	0.175	24.4	-1.1	16.0	39.4	Line 1	26.60	-
QP	0.175	28.0	-1.1	16.0	43.0	Line 1	-	36.01
AV	2.088	5.7	-0.5	16.2	21.4	Line 1	38.59	-
QP	2.088	14.0	-0.5	16.2	29.7	Line 1	-	43.25
AV	2.407	2.8	-0.5	16.2	18.5	Line 1	41.46	-
QP	2.407	12.6	-0.5	16.2	28.3	Line 1	-	44.67
AV	11.999	5.8	-0.1	15.8	21.5	Line 1	38.50	-
QP	11.999	11.7	-0.1	15.8	27.4	Line 1	-	45.58
AV	16.000	12.4	0.0	15.7	28.1	Line 1	31.85	-
QP	16.000	15.8	0.0	15.7	31.4	Line 1	-	41.55
AV	0.154	27.1	-1.3	16.0	41.9	Neutral	24.11	-
QP	0.154	30.3	-1.3	16.0	45.1	Neutral	-	33.93
AV	0.171	24.9	-1.1	16.0	39.8	Neutral	26.19	-
QP	0.171	28.2	-1.1	16.0	43.1	Neutral	-	35.87
AV	2.034	4.0	-0.5	16.2	19.7	Neutral	40.35	-
QP	2.034	14.5	-0.5	16.2	30.2	Neutral	-	42.82
AV	2.407	2.9	-0.5	16.2	18.6	Neutral	41.36	-
QP	2.407	13.0	-0.5	16.2	28.8	Neutral	-	44.23
AV	12.000	6.0	-0.1	15.8	21.7	Neutral	38.35	-
QP	12.000	11.8	-0.1	15.8	27.5	Neutral	-	45.46
AV	16.000	12.2	0.0	15.7	27.9	Neutral	32.15	-
QP	16.000	15.6	0.0	15.7	31.3	Neutral	-	41.71

The highest emission measured was at **0.151 MHz**, which was **23.69 dB** below the limit.

- “Type” refers to the type of measurement performed. The type of measurement made is based on the requirements of the particular standard:
  - PK = Peak Measurement: RBW is 9 kHz, VBW is 3 MHz
  - QP = Quasi-Peak Measurement: RBW is 9 kHz, VBW is 3 MHz, and QP Detection is ENABLED
  - AV = Video Average Measurement: RBW is 9 kHz, VBW is 10 Hz
- The “Final” emissions level is attained by taking the “Level” and adding the “Transducer” factor and the “Gain/Loss” factor. (Sample Calculation: 40.2 dBuV + 1.6 dB + 16.3 dB = 58.1 dBuV. **Important Note:** This is a sample calculation only for the purpose of demonstration, and does not reflect data in this report.)
- The “TestPoint” indicates which AC or DC input power line or which I/O cable the measurement was made on.
- The “Margin” is with reference to the emissions limit. A positive number indicates that the emission measurement is below the limit. A negative number indicates that the emission measurement exceeds the limit.
- The PRESCAN is a peak measurement and is performed with the RBW set to 9 kHz, and the VBW set to 3 MHz



## Conducted Emissions, FCC Part 15

Manufacturer: Tensitron  
Customer Representative: Chris Crosby  
Model: STX250-1  
Standard Referenced: FCC Part 15

Project Number: B40717  
Test Area: 10m1  
S/N: 443VX  
Date: July 28, 2014

B40717-11-CE.doc

FR0100




Figure B1: Conducted Emissions Prescan, Line 1, 0.150MHz to 30MHz, Peak Measurements



## Conducted Emissions, FCC Part 15

Manufacturer: Tensitron  
Customer Representative: Chris Crosby  
Model: STX250-1  
Standard Referenced: FCC Part 15

Project Number: B40717  
Test Area: 10m1  
S/N: 443VX  
Date: July 28, 2014

B40717-11-CE.doc

FR0100




Figure B2: Conducted Emissions Prescan, Neutral, 0.150MHz to 30MHz, Peak Measurements



## Conducted Emissions, FCC Part 15

Manufacturer:	Tensitron
Customer Representative:	Chris Crosby
Model:	STX250-1
Standard Referenced:	FCC Part 15

Project Number:	B40717
Test Area:	10m1
S/N:	443VX
Date:	July 28, 2014

B40717-11-CE.doc

FR0100



Figure B3: Conducted Emissions Test Setup - Front

## Conducted Emissions, FCC Part 15

Manufacturer: Tensitron  
Customer Representative: Chris Crosby  
Model: STX250-1  
Standard Referenced: FCC Part 15

Project Number: B40717  
Test Area: 10m1  
S/N: 443VX  
Date: July 28, 2014

B40717-11-CE.doc

FR0100



Figure B4: Conducted Emissions Test Setup - Right

## Conducted Emissions, FCC Part 15

Manufacturer:	Tensitron
Customer Representative:	Chris Crosby
Model:	STX250-1
Standard Referenced:	FCC Part 15

B40717-11-CE.doc

Project Number:	B40717
Test Area:	10m1
S/N:	443VX
Date:	July 28, 2014

FR0100



Figure B5: Conducted Emissions Test Setup - Back

## Conducted Emissions, FCC Part 15

Manufacturer:	Tensitron
Customer Representative:	Chris Crosby
Model:	STX250-1
Standard Referenced:	FCC Part 15

B40717-11-CE.doc

Project Number:	B40717
Test Area:	10m1
S/N:	443VX
Date:	July 28, 2014

FR0100



Figure B6: Conducted Emissions Test Setup - Left



## Conducted Emissions, FCC Part 15

Manufacturer:	Tensitron	Project Number:	B40717
Customer Representative:	Chris Crosby	Test Area:	10m1
Model:	STX250-1	S/N:	443VX
Standard Referenced:	FCC Part 15	Date:	July 28, 2014
B40717-11-CE.doc		FR0100	

### Test Equipment List

ID Number	Manufacturer	Model #	Serial #	Description	Cal Date	Cal Due
1017	Pacific Power	TMX 140	0256	4 kVA, 50 Hz Power Source	NA	NA
1194	Solar	9252-50-R-24-BNC	042012	LISN	03/18/2014	03/18/2015
1200	Agilent Technology	11947A	3107A03807	Transient Limiter, 9 kHz to 200 MHz	01/21/2014	01/21/2015
1223	Hewlett Packard	85650A	3303A01859	Quasi-Peak Adaptor	03/13/2014	03/13/2015
1335	Hewlett Packard	85662A	2542A10937	Spectrum Analyzer Display	03/13/2014	03/13/2015
1336	Hewlett Packard	8566B	2532A02062	Spectrum Analyzer RF Section	03/13/2014	03/13/2015
1338	Hewlett Packard	85685A	3506A01551	RF Preselector	03/13/2014	03/13/2015
1211	Solar	8131-24	863974	24kHz, 100 dB, High Pass Filter	NA	NA
1539	Extech Instruments	445715	Z316007	Hygro-Thermometer	03/21/2014	03/21/2015

## **APPENDIX C**

### **Product Data Sheet**



## 1.0 Client Information

Client Information	
Manufacturer Name	Tensitron
Address	733 South Bowen Street
City	Longmont
State	CO
Zip Code	80501
Client Representative	Chris Crosby (CEPD)
Title	President
Phone	(303) 415-1112 Ext 13
Fax	(720) 306-4445
Email	ccrosby@cepd.com

## 2.0 Product Information - General

Product Information	
Product Name (as it should appear on test report)	STX250-1
Model Number (of UUT to be tested)	STX250-1
Functional description of product (what is it, what does it do, etc.)	Electronic Tension Gauge
List all modes of operation	BATTERY POWER AND/OR POWER SUPPLY
Can modes be operated simultaneously? If so, explain.	YES
What mode(s) will be used for testing?	POWER SUPPLY
Product type (IT, Medical, Scientific, Industrial, etc.)	Industrial
Is the product an intentional radiator	No
Product Dimensions	7" X 9.8" X 2.23"
Product Weight	2-3/4 LBS
Will fork lift be required	No
Applicable Standards, if known	FCC part 15
Describe all environment(s) where product will be used (residential, commercial, industrial, etc.)	INDUSTRIAL
Does product consist of multiple components? (If yes, please describe each system component)	NO
Cycle time > 3 seconds? (If yes, how long?)	No
Highest internally generated frequency	6 MHz
Product Set-up Time	30 minutes
Boot up time in the event of an unintentional power down	< 10 seconds

Identify **ALL** I/O connections on the unit(s) under test, as well as **MAXIMUM** associated cable lengths below

Model No.	Description	I/O Type		Length (m)	Patient Connect? (See Note)	QTY
		UUT-UUT	UUT-SE			
EMSA090170-P7P-SZ-C	Power supply			1.5		

Note: "Patient Connect" column applies only to medical devices.

### 3.0 Power

Power Requirements	
Does/can product connect to AC mains? (If so, can the UUT function when connected to AC?)	Yes
Input Voltage Rating as it appears on unit, power supply, or power brick	100-240, 50/60 Hz
Input Current (specify @ 230 Vac/50 Hz)	Less than 0.3A
Single or Multi-Phase (If multi-phase, specify delta or wye)	Single
Is input power connector two-prong (Hot & Neutral) or 3-prong (H, N, Ground)	Two-prong
Does UUT have more than 1 power cord? (If yes, explain.)	No

### 4.0 Unit Under Test (UUT) – Detailed Information

UUT Hardware			
Condition		New	
Configuration During Test		Charger connected	
Input Power		Battery powered and with charger connected	
UUT Components			
Name	Model No.	Serial No.	Description
STX250-1	STX250-1	443VX	Aircraft Tension Meter
I/O Cabling			
See Section 2.0 for details			
UUT Software/Firmware			
Name	Version/Revision	Functionality	
Tensitron_LCD	2.01.109	Full function, production firmware	
UUT Operating Conditions			
List all frequencies generated/used by the product.		6MHz, 500KHz, both internal to the unit.	
How will product be exercised during test?		Pre-set load reading, no user intervention required.	
How will product be monitored during test?		Visual monitoring of display	
What are the product’s critical parameters?		Display reading to stay within +/-2% during testing	
Specify tolerance of all critical parameters.		Tension reading, +/- 2%	




## 5.0 Support Equipment (SE) – Detailed Information

Support Equipment (SE)			
Name	Model No.	Serial No.	Description
None			

SE I/O Cabling				
Model No.	Description	Shielded?	Length	Quantity
None				

SE Software/Firmware		
Name	Version/Revision	Functionality
None		

## 6.0 Block Diagram



## **APPENDIX D**

### **EMI Test Log**



## EMI Test Log

Manufacturer:	Tensitron	Project Number:	B40717
Model:	STX-1000-1	S/N:	443VX
Customer Representative:	Chris Crosby		
Standard Referenced:	FCC Part 15		

FR0105

## 10m Emissions

Test	Test Code	Date	Event	O T	Time (hrs)	Result	Initials
RE	1312	July 28, 2014 0800-0930	Test#1: 30MHz – 1GHZ, 8 rads, 4 heights, 3 second dwell, ref level =80dB, 10 meter distance 120Vac/60Hz Pretest verification complete		1.5	Pass	KJ
RE	1311	0930-1100	Test#2: 1GHz – 18GHZ, 16 rads, 2 heights, 3 second dwell, ref level =107dB, 3 meter distance 120Vac/60Hz		1.5	Pass	KJ
RE	1311	1100-1130	Test#3: 18GHz – 30GHz 120Vac/60Hz		0.5	Pass	KJ
CE	2311	1130-1200	Test#4: 150KHz – 30MHz 120Vac/60Hz		0.5	Pass	KJ

Regular hours:	4.0
Overtime/Prem hours:	
Total hours:	4.0

## **APPENDIX E**

### **Laboratory Accreditations**



**Nemko Laboratory  
Authorization**  
**Authorization: ELA 215**

**EMC Laboratory:** EMC Integrity, Inc.  
1736 Vista View Drive  
Longmont, Colorado 80504  
USA

**Scope of  
Authorization:** All CENELEC standards [ENs] for EMC that are listed on the  
accompanying page, and all of the corresponding CISPR,  
IEC and ISO EMC standards that are listed on the  
accompanying page.

Nemko has assessed the quality assurance system, the testing facilities, qualifications and testing practices of the relevant parts of the organization. The quality assurance system of the Laboratory has been validated against ISO/IEC 17025 or equivalent. The laboratory also fulfils the conditions described in Nemko Document NLA -10. During the visit by the Nemko representative it was found that the Laboratory is capable of performing tests within the Scope of the Authorisation.

Accordingly, Nemko will normally accept test results from the laboratory on a partial or complete basis for certification of the products.

In order to maintain the Authorisation, the information given in the pertinent NLA-10 must be carefully followed. Nemko is to be promptly notified about any changes in the situation at the Laboratory, which may affect the basis for this Authorisation. The Authorisation may be withdrawn at any time if the conditions are no longer considered to be fulfilled.

**The Authorisation is valid through June 30, 2015.**

Dallas, Texas, USA.

For and on behalf of Nemko AS:

T.B. Ketterling,  
Nemko ELA Co-ordinator  
Region: North America

## SCOPE OF AUTHORIZATION

Capability to perform a basic test implies also that any product (family) standard calling up this basic test is also within the scope if mentioned below or not.

Generic & Product –Family Standards		
EN 55011 :1998+A1 :1999 +A2 :2002 EN 55011:2007 +A2:2007 EN 55011:2009 +A1:2010 CISPR 11:1997 (Modified) + A1:1999 + A2:2002 CISPR 11 Ed. 4.1 CISPR 11 Ed 5.1 (2010-7)	EN55014:1997 +A1:2008 EN 55014-1:2006 +A1:2009 EN 55014-1:2000 + A1:2001 + A2:2002 CISPR 14-1:2000 + A1:2001 + A2:2002 CISPR 14-1:2005 +A1:2008 CISPR 14-1 Ed. 5.0	EN 55014-2:1997 + A1:2001 CISPR 14-2:1997 + A1:2001 +A2:2008 CISPR 14-2 Ed. 1.2
EN 55022: 1998+ A1:2000, +A2:2003 CISPR 22: 2003+ A1:2004 CISPR 22:2005 (Modified) EN55022:2006  CISPR 22 Ed. 5.2 CISPR 22 Ed. 6.0 (2008-09) EN 55022 +A1: 2007  EN 55022:2010	EN 55024: 1998 +A1:2001, +A2:2003 CISPR 24: 1997 +A1:2001, +A2:2002 CISPR 24 Ed. 1.0  EN 55024:2010	EN 61000-6-1 :2007 IEC 61000-6-1 Ed. 2.0 EN 61000-6-1: 2001
EN 61000-6-2:2005 IEC 61000-6-2 Ed. 2.0	EN 61000-6-3 :2007 IEC 61000-6-3 Ed. 2.0 EN 61000-6-3: 2001 + A1 :2004	IEC 61000-6-2 Ed. 2.0 EN 61000-6-2: 2005 IEC 61000-6-2: 2005 EN 61000-6-2: 2001
EN 61326:1997 +A1:1998 + A2:2001 +A3:2003 IEC 61326:1997 + A1:1998 + A2:2000  EN 61326-1 Ed. 1.0 EN 61326-1 :2013 IEC 61326-1 Ed. 2.0 (2012-07) IEC 61326:2006	EN 60601-1-2:2001 + A1:2006 IEC 60601-1-2:2001  EN 60601-1-2:2007 IEC 60601-1-2:2007 (Ed. 3.0)	EN 55103-1:1996 EN 55103-2 :1996  EN 55103-1:2005 EN 55103-2:2005
EN 300 386 V.1.3.1 EN 300 386 V.1.3.3 EN 300 386 V.1.4.1	EN 61000-3-3: 1995, +A1:2001 +A2:2005 IEC 61000-3-3: 1994, +A1:2001 +A2:2005 EN 61000-3-3:2008	EN 61000-3-2: 2000 +A2 :2005 IEC 61000-3-2: 2000 (Modified) +A1:2001 +A2:2004 EN 61000-3-2:2006
EN 50130-4: 1995 + A1:1998 + A2:2002 EN 50130-4:2011	ETSI EN 301 489-x ETSI EN 300 220-x	ETSI EN 300 339 Ed. 1

T.B. Ketterling

T.B. Ketterling, Nemko ELA Co-ordinator

EMC INTEGRITY, INC.  
Test Report # ETRB40717

Basic Standards		
EN 61000-4-2:1995, +A1:1998, +A2:2000 IEC 61000-4-2:1995, +A1:1998, +A2:2000 EN 61000-4-2 : 2009 EN 61000-4-2 :2008 (ed. 2) IEC 61000-4-2:2001 (ed. 1.2)	EN 61000-4-3:2002, +A1:2002 IEC 61000-4-3:2002, +A1:2002 EN 61000-4-3 :2006 +A1 :2006 +A2 :2006 IEC 61000-4-3 (Ed. 3.0) +A1 :2007 +A2 :2010	EN 61000-4-4:1995, +A1:2002, +A2:2002 IEC 61000-4-4:1995, +A1:2000, +A2:2001 EN 61000-4-4:2004 IEC 61000-4-4 Ed. 2.0 IEC 61000-4-4:2012
EN 61000-4-5:1995, +A1:2001 IEC 61000-4-5:1995, +A1:2000 EN 61000-4-5 :2006 IEC 61000-4-5 Ed. 2.0	EN 61000-4-6:1996, +A1:2001 IEC 61000-4-6:1996, +A1:2000 EN 61000-4-6 : 2009 IEC 61000-4-6 Ed. 2.2 IEC 61000-4-6 :2008	EN 61000-4-8:1994, +A1:2001 IEC 61000-4-8:1994, +A1:2001 IEC 61000-4-8 Ed. 1.1 IEC 61000-4-8 :2001 IEC 61000-4-8 :2009 EN 61000-4-8 :2010
EN 61000-4-11:2004 IEC 61000-4-11 Ed. 2.0 EN 61000-4-11:1994, +A1:2000 IEC 61000-4-11:1994, +A1:2000	BLANK	BLANK

T.B. Ketterling

T.B. Ketterling, Nemko ELA Co-ordinator

3(3)

NLA 3 ED3

United States Department of Commerce  
National Institute of Standards and Technology



---

## Certificate of Accreditation to ISO/IEC 17025:2005

---

NVLAP LAB CODE: 200737-0

**EMC Integrity, Inc.**  
Longmont, CO

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,  
listed on the Scope of Accreditation, for:*


### **ELECTROMAGNETIC COMPATIBILITY AND TELECOMMUNICATIONS**

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.  
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality  
management system (refer to joint ISO-ILAC-IAF Communiqué dated January 2009).*

2014-07-01 through 2015-06-30

*Effective dates*



  
For the National Institute of Standards and Technology

NVLAP-01C (REV. 2009-01-28)





**National Voluntary  
Laboratory Accreditation Program**



**SCOPE OF ACCREDITATION TO ISO/IEC 17025:2005**

**EMC Integrity, Inc.**  
1736 Vista View Drive  
Longmont, CO 80504  
Mr. Vincent W. Greb  
Phone: 303-776-7249 Fax: 303-776-7314  
E-Mail: vinceg@emcintegrity.com  
URL: <http://www.emcintegrity.com>

**ELECTROMAGNETIC COMPATIBILITY  
AND TELECOMMUNICATIONS**

**NVLAP LAB CODE 200737-0**  
Scope Revised: 2014-07-17

***NVLAP Code    Designation / Description***

**Emissions Test Methods**

12/100063c	IEC 61000-6-3 (1996), EN 61000-6-3 (2001), A1 (2004): Electromagnetic Compatibility (EMC) - Part 6: Generic standards - Section 3: Emission standard for residential, commercial, and light-industrial environments.
12/610006m	EN 61000-6-4 (2007): Electromagnetic Compatibility (EMC) - Part 6-4: Generic Standards - Emission Standard for Industrial Environments
12/61326da	IEC 61326-1 Ed. 2.0 (2012): Electrical equipment for measurement, control and laboratory use - EMC requirements - Part 1: General requirements
12/CIS11f	AS/NZS CISPR 11 (2002): Industrial, scientific and medical (ISM) radio frequency equipment - Electromagnetic disturbance characteristics - Limits and methods of measurement
12/CIS11g	IEC/CISPR 11, Ed. 4.1 (2004-06): Industrial, scientific and medical (ISM) radio-frequency equipment - Electromagnetic disturbance characteristics - Limits and methods of measurements
12/CIS11h	AS/NZS CISPR 11 (2004): Industrial, scientific and medical (ISM) radio frequency equipment - Electromagnetic disturbance characteristics - Limits and methods of measurement
12/CIS11i	IEC/CISPR 11, Ed. 4.1 (2004-06) + A1(2004): Industrial, scientific and medical (ISM) radio frequency equipment - Electromagnetic disturbance characteristics - Limits and methods of measurement

2014-07-01 through 2015-06-30

*Effective dates*

*For the National Institute of Standards and Technology*



**National Voluntary  
Laboratory Accreditation Program**



**ELECTROMAGNETIC COMPATIBILITY  
AND TELECOMMUNICATIONS**

**NVLAP LAB CODE 200737-0**

Scope Revised: 2014-07-17

<i>NVLAP Code</i>	<i>Designation / Description</i>
12/CIS11j	EN 55011 (1998) + A1(1999), A2(2002): Industrial, scientific and medical (ISM) radio frequency equipment - Electromagnetic disturbance characteristics - Limits and methods of measurement
12/CIS11k	IEC/CISPR 11 (2003), EN 55011 (1998), A2(2002): Limits and Methods of Measurement of Electromagnetic Disturbance Characteristics of Industrial, Scientific, and Medical Radio-Frequency Equipment
12/CIS11m2	EN 55011 (2009) + A1 (2010): Industrial, scientific and medical (ISM) radio-frequency equipment - Electromagnetic disturbance characteristics - Limits and methods of measurement
12/CIS11p	IEC/CISPR 11 Ed. 5 (2009-05): Industrial, scientific and medical equipment - Radio-frequency disturbance characteristics - Limits and methods of measurement
12/CIS14b1	AS/NZS CISPR 14-1 (2003): Electromagnetic Compatibility - Requirements for household appliances, electric tools and similar apparatus - Part 1: Emission
12/CIS14x	IEC/CISPR 14-1, Ed. 4 (2003): Electromagnetic Compatibility - Requirements for household appliances, electric tools and similar apparatus - Part 1: Emission
12/CIS22	IEC/CISPR 22 (1997) & EN 55022 (1998) + A1(2000): Limits and methods of measurement of radio disturbance characteristics of information technology equipment
12/CIS22a	IEC/CISPR 22 (1993) and EN 55022 (1994): Limits and methods of measurement of radio disturbance characteristics of information technology equipment, Amendment 1 (1995) and Amendment 2 (1996)
12/CIS22a4	IEC/CISPR 22 (1993) & EN 55022 (1994)+A1(1995), A2(1997): Limits and methods of measurement of radio disturbance characteristics of information technology equipment
12/CIS22b	CNS 13438 (1997): Limits and Methods of Measurement of Radio Interference Characteristics of Information Technology Equipment
12/CIS22c	IEC/CISPR 22, Fourth Edition (2003-04) & EN 55022 (1998): Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement

2014-07-01 through 2015-06-30

*Effective dates*

*For the National Institute of Standards and Technology*



**National Voluntary  
Laboratory Accreditation Program**



**ELECTROMAGNETIC COMPATIBILITY  
AND TELECOMMUNICATIONS**

**NVLAP LAB CODE 200737-0**  
Scope Revised: 2014-07-17

<i>NVLAP Code</i>	<i>Designation / Description</i>
12/CIS22c1	IEC/CISPR 22, Edition 5 (2005) and EN 55022 (1998): Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement
12/CIS22c3	IEC/CISPR 22, Edition 5 (2005) + A1(2005): Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement
12/CIS22c4	EN 55022 (1998) + A1(2000) + A2(2003): Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement
12/CIS22f	CNS 13438 (2006) (up to 6GHz): Limits and Methods of Measurement of Radio Interference Characteristics of Information Technology Equipment
12/CIS22i	IEC/CISPR 22, Edition 5.2 (2006-03): Limits and Methods of Measurement of Radio Disturbance Characteristics of Information Technology Equipment
12/CIS22j	EN 55022 (2006): Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement
12/CIS22j1	EN 55022 (2006) + A1 (2007): Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement
12/CIS22j2	EN 55022:2010: Information technology equipment. Radio disturbance characteristics. Limits and methods of measurement
12/CIS22k	IEC/CISPR 22 (2008-09): Limits and Methods of Measurement of Radio Disturbance Characteristics of Information Technology Equipment
12/EM02d	IEC 61000-3-2, Edition 2.2 (2004-11): Electromagnetic compatibility (EMC) - Part 3-2: Limits - Limits for harmonic current emissions (equipment input current $\leq 16$ A per phase)
12/EM02k	GB 17625.1 (2003): Electromagnetic compatibility (EMC) - Part 3: Limits - Section 2. Limits for harmonic current emissions (equipment input current $\leq 16$ A per phase)
12/EM03b	IEC 61000-3-3, Edition 1.1(2002-03) & EN 61000-3-3, A1(2001): EMC - Part 3-3: Limits - Limitations of voltage changes, voltage fluctuations and flicker, in public low-voltage supply-systems, for equipment with rated current $\leq 16$ A per phase and not subject to conditional connections

2014-07-01 through 2015-06-30

*Effective dates*

*For the National Institute of Standards and Technology*



**National Voluntary  
Laboratory Accreditation Program**



**ELECTROMAGNETIC COMPATIBILITY  
AND TELECOMMUNICATIONS**

**NVLAP LAB CODE 200737-0**  
Scope Revised: 2014-07-17

<i>NVLAP Code</i>	<i>Designation / Description</i>
12/EM03g	IEC 61000-3-3, Edition 1.1 (2003) +A2 (2005): EMC Part 3-3: Limits - Limitations of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current $\leq 16$ A per phase and not subject to conditional connections
12/EM12c	IEC 61000-3-12 Ed. 2.0 (2011): Electromagnetic compatibility (EMC) - Part 3-12: Limits - Limits for harmonic currents produced by equipment connected to public low-voltage systems with input current $>16$ A and $= 75$ A per phase
12/EM12d	EN 61000-3-12 (2011): Electromagnetic Compatibility (EMC) - PART 3-12: Limits for harmonic currents produced by equipment connected to public low-voltage systems with input current greater than 16A and less than or equal to 75A
12/F18	FCC OST/MP-5 (1986): FCC Methods of Measurement of Radio Noise Emissions for ISM Equipment (cited in FCC Method 47 CFR Part 18 - Industrial, Scientific, and Medical Equipment)
12/FCC15b	ANSI C63.4 (2003) with FCC Method 47 CFR Part 15, Subpart B: Unintentional Radiators
12/FCC15bb	ANSI C63.4 (2009) with FCC Method 47 CFR Part 15, Subpart B: Unintentional Radiators
12/KN11d1	KN11 (Annex 3) with RRA Announce 2008-11 (Dec. 16, 2008): Conformity Assessment Procedure for Electromagnetic Interference; With KN 11 (Annex 3)
12/KN16	Korea RRA Notice No. 2008-11 (Dec. 16, 2008): Conformity Assessment Procedures for Electromagnetic Interference using KN 16-1-1, KN 16-1-2, KN 16-1-3, KN 16-1-4, KN 16-1-5, KN 16-2-1, KN 16-2-2, KN 16-2-3, KN 16-2-4 (2008-05)
12/KN22	KN22 with RRL Notice No. 2005-82 (Sept. 29, 2005): RRL Notice No. 2005-82: Technical Requirements for Electromagnetic Interference Annex 8 (KN-22), RRL Notice No. 2005-131: Conformity Assessment Procedures for Electromagnetic Interference
12/KN22e	KN22 (2008-5) with RRL Notice No. 2008-3 (May 20, 2008): Conformity Assessment Procedure for Electromagnetic Interference; With KN 22
12/KN22f	KN22 (Annex 5) with RRA Announce 2010-5 (Dec 24, 2010): Conformity Assessment Procedure for Electromagnetic Interference; With KN 22 (Annex 5)

2014-07-01 through 2015-06-30

*Effective dates*

*For the National Institute of Standards and Technology*



**National Voluntary  
Laboratory Accreditation Program**



**ELECTROMAGNETIC COMPATIBILITY  
AND TELECOMMUNICATIONS**

**NVLAP LAB CODE 200737-0**  
Scope Revised: 2014-07-17

***NVLAP Code      Designation / Description***

12/RRA04a	RRA 2014-8 and RRA 2014-37 (June 23, 2014): Technical Requirements and Test Methods for Electromagnetic Interference; K only (See specific Annexes listed on scope)
12/RRA105	RRA Announce 2010-5, K only (December 24, 2010): Conformity Assessment Procedure for Electromagnetic Interference (K only)
12/RRA1118	RRA Public Notification 2011-18, K only (July 5, 2011): Technical Requirements for Electromagnetic Interference (K only)
12/T51	AS/NZS CISPR 22 (2002) and AS/NZS 3548 (1997): Electromagnetic Interference - Limits and Methods of Measurement of Information Technology Equipment
12/T51b1	AS/NZS CISPR 22 (2009): Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement
12/TCVNa	TCVN 7189:2009 (CISPR 22:2006): Information Technology Equipment-Radio disturbance characteristics - Limits and methods of measurement
12/VCCIe	Agreement of VCCI V-3 (2009.04): Agreement of Voluntary Control Council for Interference by Information Technology Equipment - Technical Requirements: V-3/2009.04 (radiated disturbance above 1 GHz)
12/VCCIg	Agreement of VCCI V-3 (2011.04): Agreement of VCCI Council - Technical Requirements: V-3/2011.04 (including radiated disturbance above 1 GHz)
12/VCCLi	Agreement of VCCI V-3 (2013.04): Agreement of VCCI Council - Technical Requirements: V-3/2013.04 (including radiated disturbance above 1 GHz)

**Immunity Test Methods**

12/610006h	IEC 61000-6-1, 2nd edition (2005-03): Electromagnetic compatibility (EMC) - Part 6: Generic standards - Section 1: Immunity for residential, commercial and light-industrial environments
12/610006i	IEC 61000-6-2, Edition 2.0 (2005-01): Electromagnetic compatibility (EMC) - Part 6-2: Generic standards - Immunity for industrial environments

2014-07-01 through 2015-06-30

*Effective dates*

*For the National Institute of Standards and Technology*



**National Voluntary  
Laboratory Accreditation Program**



**ELECTROMAGNETIC COMPATIBILITY  
AND TELECOMMUNICATIONS**

**NVLAP LAB CODE 200737-0**  
Scope Revised: 2014-07-17

<i>NVLAP Code</i>	<i>Designation / Description</i>
12/61326aa	EN 61326-1:2013: Electrical equipment for measurement, control and laboratory use - EMC requirements - Part 1: General requirements
12/CIS24g	CISPR 24 ed2.0 (2010-08): Information technology equipment - Immunity characteristics - Limits and methods of measurement
12/CIS24h	EN 55024 (2010): Information technology equipment. Immunity characteristics. Limits and methods of measurement
12/I01b	IEC 61000-4-2 (2001); EN 61000-4-2 (2001), A2 (2001): Electrostatic Discharge Immunity Test
12/I01c	EN 61000-4-2 +A1(1998) +A2(2001): Electrostatic Discharge Immunity Test
12/I01d	IEC 61000-4-2, Ed. 2.0 (2008-12): Electromagnetic compatibility (EMC) - Part 4-2: Testing and measurement techniques - Electrostatic discharge immunity test
12/I01f	EN 61000-4-2 (2009-05): Electromagnetic compatibility (EMC) - Part 4-2 : Testing and measurement techniques - Electrostatic discharge immunity test
12/I02b	IEC/EN 61000-4-3, Ed. 2.1 (2002), A1 (2002); EN 61000-4-3: Radiated, radio-frequency, electromagnetic field immunity test
12/I02c	IEC 61000-4-3 (1995), A1(1998), A2(2000): Radiated, radio-frequency, electromagnetic field immunity test
12/I02f	EN 61000-4-3 (2002) + A1(2002): Radiated, radio-frequency, electromagnetic field immunity test
12/I02ggg	IEC 61000-4-3, Ed. 3.0 (2006-02) + A1 (2007) + A2 (2010): Electromagnetic compatibility (EMC) - Part 4-3: Testing measurement techniques - Radiated, radio-frequency, electromagnetic field immunity test
12/I02hhh	EN 61000-4-3 (2006) +A1 (2008) + A2 (2010): Electromagnetic compatibility (EMC). Testing and measurement techniques. Radiated, radio- Frequency, electromagnetic field immunity test

2014-07-01 through 2015-06-30

*Effective dates*

*For the National Institute of Standards and Technology*



**National Voluntary  
Laboratory Accreditation Program**



**ELECTROMAGNETIC COMPATIBILITY  
AND TELECOMMUNICATIONS**

**NVLAP LAB CODE 200737-0**  
Scope Revised: 2014-07-17

<i>NVLAP Code</i>	<i>Designation / Description</i>
12/I03c	IEC 61000-4-4, Ed. 2.0 (2004-07): Electromagnetic compatibility (EMC) - Part 4-4: Testing and measurement techniques - Electrical fast transient/burst immunity test
12/I03e	EN 61000-4-4 (2004): Electromagnetic compatibility (EMC) - Part 4-4: Testing and measurement techniques - Electrical fast transient/burst immunity test
12/I04aa	IEC 61000-4-5, Ed. 2.0 (2005-11); EN 61000-4-5: Electromagnetic Compatibility (EMC) - Part 4-5: Testing and measurement techniques - Surge immunity test
12/I04b	IEC 61000-4-5 (2001), A1(2000); EN 61000-4-5(2001), A1(2000): Surge Immunity Test
12/I04d	BS EN 61000-4-5 (2006): Electromagnetic compatibility (EMC). Testing and measurement techniques. Surge immunity test
12/I05d	IEC 61000-4-6, Ed. 2.1 (2004); EN 61000-4-6: Electromagnetic compatibility (EMC) - Part 4-6: Testing and measurement techniques - Immunity to conducted disturbances, induced by radio-frequency fields
12/I05e	EN 61000-4-6 (1996) + A1 (2001): Immunity to Conducted Disturbances, Induced by Radio Frequency Fields
12/I05fl	IEC 61000-4-6 Ed. 3.0 (2008): Electromagnetic compatibility (EMC) - Part 4-6: Testing and measurement techniques - Immunity to conducted disturbances, induced by radio-frequency fields
12/I05j	EN 61000-4-6 (2009): Electromagnetic compatibility (EMC) - Part 4-6: Testing and measurement techniques - Immunity to conducted disturbances, induced by radio-frequency fields
12/I06b	IEC 61000-4-8 (2001), A1(2000); EN 61000-4-8 (2001),A1(2000): Power Frequency Magnetic Field Immunity Test
12/I06c	EN 61000-4-8 (1993) + A1 (2001): Power Frequency Magnetic Field Immunity Test
12/I06e	IEC 61000-4-8 (2009): Electromagnetic compatibility (EMC) - Part 4-8: Testing and measurement techniques - Power frequency magnetic field immunity test

2014-07-01 through 2015-06-30

*Effective dates*

*For the National Institute of Standards and Technology*



**National Voluntary  
Laboratory Accreditation Program**



**ELECTROMAGNETIC COMPATIBILITY  
AND TELECOMMUNICATIONS**

**NVLAP LAB CODE 200737-0**  
Scope Revised: 2014-07-17

<i>NVLAP Code</i>	<i>Designation / Description</i>
12/I06f	EN 61000-4-8:2010: Electromagnetic compatibility (EMC). Testing and measurement techniques. Power frequency magnetic field immunity test
12/I07c	IEC 61000-4-11, Ed. 2 (2004-03) & EN 61000-4-11: Electromagnetic compatibility (EMC) - Part 4-11: Testing and measurement techniques - Voltage dips, short interruptions and voltage variations immunity tests
12/I07e	EN 61000-4-11 (1994), A1 (2001): Voltage Dips, Short Interruptions and Voltage Variations Immunity Tests
12/I07f	EN 61000-4-11 (2004): Voltage Dips, Short Interruptions and Voltage Variations Immunity Tests
12/KN11a	KN 61000-4-11 with RRL Notice No. 2005-130 (Dec 27, 2005): Voltage Dips, Short Interruptions and Voltage Variations Immunity Tests
12/KN11f	KN 61000-4-11 (2008-5); RRL Notice No. 2008-4 (May 20, 2008): Voltage Dips, Short Interruptions and Voltage Variations Immunity Tests
12/KN11h	KN 61000-4-11 (Annex 1-7) RRA Announce 2010-6 (Dec.24, 2010): Conformity Assessment Procedure for EMS (Voltage Dips, Short Interruptions and Voltage Variations Immunity tests)
12/KN24	KN24 (December 2005) with RRL Notice No. 2005-83: Information Technology Equipment - immunity characteristics - limits and methods of measurements
12/KN24d	KN 24 (2008-5) with RRL Notice No. 2008-4 (May 20, 2008): Information Technology Equipment - immunity characteristics - limits and methods of measurements
12/KN24e	KN 24 (Annex 5) with RRA Announce 2010-6 (Dec. 24, 2010): Conformity Assessment Procedure for EMS (Information technology equipment - Immunity characteristics - Limits and methods of measurement)
12/KN2a	KN 61000-4-2 with RRL Notice No. 2005-130 (Dec. 27, 2005): Electrostatic Discharge Immunity Test

2014-07-01 through 2015-06-30

*Effective dates*

*For the National Institute of Standards and Technology*





**National Voluntary  
Laboratory Accreditation Program**



**ELECTROMAGNETIC COMPATIBILITY  
AND TELECOMMUNICATIONS**

**NVLAP LAB CODE 200737-0**  
Scope Revised: 2014-07-17

<i>NVLAP Code</i>	<i>Designation / Description</i>
12/KN2c	KN 61000-4-2 (2008-5); RRL Notice No. 2008-4 (May 20, 2008): Electrostatic Discharge Immunity Test
12/KN2e	KN 61000-4-2 (Annex 1-1) RRA Announce 2010-6 (Dec. 24, 2010): Conformity Assessment Procedure for EMS (Electrostatic Discharge Immunity Test)
12/KN3a	KN 61000-4-3 with RRL Notice No. 2005-130 (Dec. 27, 2005): Radiated, radio-frequency, electromagnetic field immunity test
12/KN3c	KN 61000-4-3 (2008-5); RRL Notice No. 2008-4 (May 20, 2008): Radiated, radio-frequency, electromagnetic field immunity test
12/KN3e	KN 61000-4-3 (Annex 1-2) RRA Announce 2010-6 (Dec. 24, 2010): Radiated, radio-frequency, electromagnetic field immunity test
12/KN4a	KN 61000-4-4 with RRL Notice No. 2005-130 (Dec. 27, 2005): Electromagnetic compatibility (EMC): Testing and measurement techniques - Electrical Fast Transient/Burst Immunity Test
12/KN4c	KN 61000-4-4 (2008-5); RRL Notice No. 2008-5 (May 20, 2008): Electromagnetic compatibility (EMC): Testing and measurement techniques - Electrical Fast Transient/Burst Immunity Test
12/KN4e	KN 61000-4-4 (Annex 1-3) RRA Announce 2010-6 (Dec. 24, 2010): Electromagnetic compatibility (EMC): Testing and measurement techniques - Electrical Fast Transient/Burst Immunity Test
12/KN5a	KN 61000-4-5 with RRL Notice No. 2005-130 (Dec. 27, 2005): Surge Immunity Test
12/KN5c	KN 61000-4-5 (2008-5); RRL Notice No. 2008-4 (May 20, 2008): Surge Immunity Test
12/KN5e	KN 61000-4-5 (Annex 1-4) RRA Announce 2010-6 (Dec. 24, 2010): Conformity Assessment Procedure for EMS (Surge Immunity Test)
12/KN6a	KN 61000-4-6 with RRL Notice No. 2005-130 (Dec. 27, 2005): Electromagnetic compatibility (EMC): Testing and measurement techniques - Immunity to conducted disturbances,

2014-07-01 through 2015-06-30

*Effective dates*

*For the National Institute of Standards and Technology*



**National Voluntary  
Laboratory Accreditation Program**



**ELECTROMAGNETIC COMPATIBILITY  
AND TELECOMMUNICATIONS**

**NVLAP LAB CODE 200737-0**  
Scope Revised: 2014-07-17

***NVLAP Code      Designation / Description***

12/KN6c	KN 61000-4-6 (2008-5); RRL Notice No. 2008-4 (May 20, 2008): Electromagnetic compatibility (EMC): Testing and measurement techniques - Immunity to conducted disturbances, induced by radio-frequency fields
12/KN6e	KN 61000-4-6 (Annex 1-5) RRA Announce 2010-6 (Dec. 24, 2010): Electromagnetic compatibility (EMC): Testing and measurement techniques - Immunity to conducted disturbances, induced by radio-frequency fields
12/KN8a	KN 61000-4-8 with RRL Notice No. 2005-130 (Dec. 27, 2005): Power Frequency Magnetic Field Immunity Test
12/KN8c	KN 61000-4-8 (2008-5); RRL Notice No. 2008-4 (May 20, 2008): Power Frequency Magnetic Field Immunity Test
12/KN8e	KN 61000-4-8 (Annex 1-6) RRA Announce 2010-6 (Dec. 24, 2010): Conformity Assessment Procedure for EMS (Power Frequency Magnetic Field Immunity Test)
12/RRA04b	RRA 2014-09 and RRA 2014-38 (June 23, 2014) K only: Technical Requirements and Test Methods for Electromagnetic Susceptibility; Korean only (See specific annexes listed on scope)
12/RRA106	RRA Public Notification 2010-6, December 24, 2010 (K only): Conformity Assessment Procedure for Electromagnetic Susceptibility (K only)
12/RRA1117	RRA Public Notification 2011-17, K only (July 5, 2011): Technical Requirements for Electromagnetic Susceptibility, K only

**Product Safety Test Methods**

12/60601ab	IEC 60601-1-2, Ed. 3.0 (2007): Medical electrical equipment - Part 1-2: General requirements for safety - Collateral standard: Electromagnetic compatibility - Requirements and tests
12/60601ac	KN 60601-1-2 (2008-5); RRL Notice No. 2008-4 (May 20, 2008): Medical electrical equipment - Part 1-2: general requirements for safety - collateral standard: electromagnetic compatibility - requirements and tests


2014-07-01 through 2015-06-30

*Effective dates*

Page 10 of 11

*For the National Institute of Standards and Technology*

NVLAP-01S (REV. 2005-05-19)



**ELECTROMAGNETIC COMPATIBILITY  
AND TELECOMMUNICATIONS**

**NVLAP LAB CODE 200737-0**  
Scope Revised: 2014-07-17

***NVLAP Code    Designation / Description***

12/60601h1    EN 60601-1-2 (2007): Medical electrical equipment - Part 1-2: General requirements for safety - Collateral standard: EMC - Requirements and tests

**MIL-STD-462 : Conducted Emissions**

12/A20    MIL-STD-461 Version F Method CE102

12/A21    MIL-STD-461 Version F Method CE106

**MIL-STD-462 : Radiated Emissions**

12/D11    MIL-STD-461 Version F Method RE102

12/D12    MIL-STD-461 Version F Method RE103

**MIL-STD-462 : Radiated Susceptibility**

12/E16    MIL-STD-461 Version F Method RS103

2014-07-01 through 2015-06-30

*Effective dates*

Page 11 of 11

A handwritten signature in black ink, appearing to read 'Mark R. Mello'.

*For the National Institute of Standards and Technology*

NVLAP-01S (REV. 2005-05-19)

**END OF REPORT**